

ANDERSON GREENWOOD WHESSOE MODELS 500A/500AE FLAME ARRESTERS

In-line deflagration flame arresters designed to prevent the propagation of subsonic flames



FEATURES

- Concentric and eccentric model variants available.
- Fabricated construction.
- Replaceable elements.
- Advanced crimped stainless steel element construction as standard. Other materials available.
- Mounted vertically or horizontally.
- Bi-directional.
- Can be used in combination with a pressure/vacuum valve.
- Independently tested and certified.
- Manufactured to ISO 9001:2008.

GENERAL APPLICATION

The 500A/500AE are used in applications with subsonic flames and mounted in process or vent lines. They can be located in the pipeline or at the end of the pipe vent.

TECHNICAL DATA

Materials:	Carbon steel, stainless steel
Sizes:	DN 6 to 1000 (NPS 1/2 to 40)
Connections:	Threaded or flanged
Temperature range:	-20° to +280°C (-4° to +536°F)
Gas groups:	IIA, IIB1, IIB2, IIB3, IIB, IIC*
Certification:	ATEX Directive 94/9/EC; PED 97/23/EC; ISO 16852

* Up to and including DN 150 (6")

ANDERSON GREENWOOD WHESOE MODELS 500A/500AE FLAME ARRESTERS

MATERIALS AND CONNECTION OPTIONS

Materials

Carbon steel and stainless steel.

Connection pipe size

Threaded DN 6 to 80 (1/8" to 3")


Flanged DN 6 to 1000 (1/8" to 40")

Gas groups

- IIA
- IIB1
- IIB2
- IIB3
- IIB
- IIC*

* Only available up to and including DN 150 (6")

500A* (DF VERSION)



* Eccentric variants are available

TEMPERATURE RANGE

Type	Gas group	Size range	Short burn	Max. temperature	Element
500A	IIB3	DN 200	No	-20/+260°C	1 x 0.38 mm
500A, 500AE	IIA	DN 12/450	Yes	-20/+60°C	1 x 0.8 mm
500A, 500AE	IIB1/IIB3	DN 12/450	Yes	-20/+60°C	1 x 0.8/0.6 mm
500A, 500AE	IIA	DN 12/450	No	-20/+165°C	1 x 0.6 mm
500A, 500AE	IIB1/IIB3	DN 12/450	No	-20/+165°C	1 x 0.38 mm
500A, 500AE	IIB	DN 12/400	Yes	-20/+60°C	1 x 0.45 mm
500A, 500AE	IIC	DN 12/150	Yes	-20/+60°C	1 x 0.15 mm
500A, 500AE	IIB	DN 12/400	No	-20/+165°C	1 x 0.3 mm
500A, 500AE	IIC	DN 12/500	No	-20/+165°C	1 x 0.15 mm

SELECTION GUIDE

Example:	500A	50	DF	100	19	60	S3	S3
Model	500A							
500A								
500AE								
Connection diameter, mm (in)								
Flanged			Threaded					
DN 6 to 1000 (1/8" to 40")			DN 6 to 80 (1/8" to 3")					
Element code								
DF								
Element diameter, DN (in)								
DN 25 to 2000 (1" to 80")								
Element width, mm (in)								
19 19 mm (0.75")			38 0.38 mm (0.015")					
38 38 mm (1.5")			15 0.15 mm (0.006")					
76 76 mm (3.0")								
Cell height, mm (in)								
80 0.80 mm (0.032")								
60 0.60 mm (0.024")								
45 0.45 mm (0.018")								
Element material								
S3 Stainless steel			C Carbon steel					
Body material								
S3 Stainless steel			C Carbon steel					

NOTES

All sizing and selection must be conducted by the factory.

Standard elements are double the pipe size.

Accessories, special materials and connections are available on request.