



BODY SIZE	BODY MATERIAL	ISO 5211 FLANGE TYPE	φA	φB	φC	φD	E*	KEY SLOT N°	F	F1	G1	G2	G3	G4	G5	H	H1	L	φM	N
065	C.S.	F25	184	200	254	50 ^{+0.2} ₋₀	14 ^{+0.120} _{+0.05}	2	54 ^{+0.2} ₋₀	-	M16x2	-	-	-	-	15	25	120	300	320
085	C.S.	F25	184	200	254	65 ^{+0.25} _{+0.15}	18 ^{+0.120} _{+0.05}	2	69.4 ^{+0.2} ₋₀	-	M16x2	-	-	-	-	15	25	130	300	380
085	C.I.	F25	184	200	254	65 ^{+0.25} _{+0.15}	18 ^{+0.120} _{+0.05}	2	69.4 ^{+0.2} ₋₀	-	M16x2	-	-	-	-	27	18	130	300	380
100	C.S.	F25	184	200	254	75 ^{+0.25} _{+0.15}	20 ^{+0.149} _{+0.065}	2	79.9 ^{+0.2} ₋₀	-	M16x2	-	-	-	-	18	25	140	300	440
130	C.S.	F30	214	230	298	110 ^{+0.25} _{+0.15}	28 ^{+0.149} _{+0.065}	2	116.4 ^{+0.2} ₋₀	-	M20x2.5	-	-	-	-	18	25	155	350	520
130	C.I.	F30	214	230	298	110 ^{+0.25} _{+0.15}	28 ^{+0.149} _{+0.065}	4	-	122.8 ^{+0.1} ₋₀	M20x2.5	-	-	-	-	30	22	175	350	520
160	C.S.	F35	244	260	356	130 ^{+0.25} _{+0.15}	32 ^{+0.18} _{+0.08}	2	137.4 ^{+0.2} ₋₀	-	M30x3.5	-	-	-	-	23	35	200	415	670
161	C.I.	F35	244	260	356	150 ^{+0.25} _{+0.15}	40 ^{+0.18} _{+0.08}	2	-	168.8 ^{+0.2} ₋₀	M30x3.5	-	-	-	-	34	39	280	410	650
161	C.S.	F40	280	300	406	150 ^{+0.25} _{+0.15}	40 ^{+0.18} _{+0.08}	4	-	168.8 ^{+0.2} ₋₀	M36	-	-	-	-	28	35	245	475	670
200	C.S.	F40	280	300	406	160 ^{+0.3} _{+0.2}	40 ^{+0.18} _{+0.08}	2	170 ^{+0.3} ₋₀	-	M36	-	-	-	-	28	40	230	475	840
201	C.S.	F40	280	300	406	160 ^{+0.3} _{+0.2}	40 ^{+0.18} _{+0.08}	4	-	180 ^{+0.3} ₋₀	M36	-	-	-	-	28	40	230	475	840
270	C.S.	F48	354	370	483	170 ^{+0.3} _{+0.2}	40 ^{+0.18} _{+0.08}	4	-	188.8 ^{+0.6} ₋₀	-	M36	-	-	-	33	45	280	560	1010
271	C.S.	F60	450	470	603	200 ^{+0.3} _{+0.2}	50 ^{+0.18} _{+0.08}	4	-	223 ^{+0.6} ₋₀	-	-	M36	-	-	53	55	330	686	1010
300	C.I.	F60	450 ^{-0.3} _{-0.6}	470 H8	603	260 ^{+0.3} _{+0.2}	56 ^{+0.18} _{+0.08}	4	-	284.8 ^{+0.6} ₋₀	-	-	M36	-	φ42 H7	65	65	630	920	1550
350	C.S.	-	660	700	813	250 ^{+0.3} _{+0.2}	56 ^{+0.18} _{+0.08}	4	-	274 ^{+0.6} ₋₀	-	-	-	M42	M42	63	70	630	920	1600

SLOTS OF KEYS ARE SHOWN WITH THE ACTUATOR IN CLOSED POSITION

[#] FOR ACTUATOR TYPE GP/GH/GO/HPG SIZE 161 IN CAST IRON SLOTS OF THE KEYS ARE N°2 AT 180°



Title COUPLING DIMENSIONS - GP/ GH / HPG / GO ACTUATOR -	
Publication number PUB083-001	Rev 00
Sheet 1 of 1	Dimensions in mm