

ANDERSON GREENWOOD SERIES HM1C HAND VALVES

A large $\frac{5}{8}$ " (16mm) bore, straight-through and roddable bi-directional flow valve for pressures to 3500 psig (241 barg)



FEATURES

- Plug stem end provides bubble-tight shutoff and ensures long valve life.
- Replaceable/repairable seat ensures long, safe and economically installed valve life.
- Large handle ensures ease of operation.
- All valves pressure tested prior to shipment. Material traceability on body is standard on request.
- PTFE packing is easily adjustable in the field.
- All packing is below the threads to eliminate contamination by the process, ensure smooth valve operation and long service life.
- Safety back seating prevents accidental stem blowout and removal under pressure.
- Upgraded bonnet lock plate prevents accidental removal under pressure.
- Standard dust cover ensures long service.
- Wide variety of inlet and outlet configurations and materials.

GENERAL APPLICATION



The HM1C is suitable for severe service, high pressure/temperature applications and features a Cv rating of 9.8, which allows for high flow capacities. It is also ideal for process conditions where potential plugging is a concern.

TECHNICAL DATA

Materials:	CS, SS
Seat:	Soft
Connections	
Inlet:	$\frac{3}{4}$ " to 1" NPT
Outlet:	$\frac{1}{2}$ " to 1" NPT
Pressure (max.):	3500 psig (241 barg)
Temperature:	-70° to 400°F (-57° to 204°C)

ANDERSON GREENWOOD SERIES HM1C HAND VALVES

PRESSURE VS TEMPERATURE



NOTE

Minimum temperature: -70°F (57 °C).

BONNET ASSEMBLY

The HM1C features a roddable soft seated design with replaceable seats, providing easy cleanout and replacement.

All stem threads are rolled and lubricated to prevent galling and reduce operating torque. The bonnet assembly has a one-piece rotating stem and plug. The stem seal is a patented PTFE or graphite packing gland which is adjustable in service. All bonnets are assembled with a bonnet locking pin to prevent accidental removal while in service and a protective dust cap is fitted to contain stem lubricant and prevent the influx of contaminants.

ANDERSON GREENWOOD SERIES HM1C HAND VALVES

SELECTION GUIDE

Example:	HM1C	S	8	D	V	SS
Materials of construction						
S	SS - 316/31L					
C	CS - carbon steel (A108CS)					
Connections (inlet/outlet)						
46	3/4" MNPT x 1/2" FNPT					
6	3/4" FNPT x 3/4" FNPT					
66	3/4" MNPT x 3/8" FNPT					
8	1" FNPT x 1" FNPT					
88	1" MNPT x 1" FNPT					
Seat						
D	Delrin®					
E	PEEK					
Packing						
V	PTFE					
Options						
OC00	Gaseous oxygen cleaned					
SS	All 316 SS construction					

NOTES

1. Call factory for optional materials.
2. $C_v = 9.8$ max.
3. 316/316L SS valves meet the requirements of NACE MR0175/ISO 15156 (for chloride conditions ≤ 50 mg/l (ppm)) and NACE MR0103-2005.

Neither Emerson, Emerson Automation Solutions, nor any of their affiliated entities assumes responsibility for the selection, use or maintenance of any product. Responsibility for proper selection, use, and maintenance of any product remains solely with the purchaser and end user.

Anderson Greenwood is a mark owned by one of the companies in the Emerson Automation Solutions business unit of Emerson Electric Co. Emerson Automation Solutions, Emerson and the Emerson logo are trademarks and service marks of Emerson Electric Co. All other marks are the property of their respective owners.

The contents of this publication are presented for informational purposes only, and while every effort has been made to ensure their accuracy, they are not to be construed as warranties or guarantees, express or implied, regarding the products or services described herein or their use or applicability. All sales are governed by our terms and conditions, which are available upon request. We reserve the right to modify or improve the designs or specifications of such products at any time without notice.