



## STANDARD SYSTEM



ATI-0730

### SYSTEM w/Q22 pH SENSOR




ATI-0648

SS-Q45H-65, RK (4/12) Page 1 of 12




## SYSTEM w/pH (BAYONET STYLE) PROBE



#### ATI-0863


### SYSTEM w/SEALED FLOWCELLS



ATI-0891

SS-Q45H-65, RK (4/12) Page 2 of 12


# 2-WIRE or REMOTE DC MODELS



ATI-0655

## NOTE: JUNCTION BOXES HAVE SAME DIMENSIONS AS 2-WIRE TRANSMITTER

### **BATTERY POWERED MODEL**





ATI-0688

SS-Q45H-65, RK (4/12) Page 3 of 12




### **WALL MOUNTING**





ATI-1033

### **PIPE MOUNTING**




NOTE: PLATE MAY BE TURNED 90° FOR VERTICAL PIPE MOUNTING

ATI-1034

SS-Q45H-65, RK (4/12) Page 4 of 12



## INTERNAL BATTERY CONFIGURATION



ATI-0827b


SS-Q45H-65, RK (4/12)

Page 5 of 12



ATI-0859


## FLOW SENSOR DIMENSIONS & OVERFLOW CELL INSTALLATION






(00-1522)

#### CI2 SEALED FLOWCELL ASSEMBLY pH SEALED FLOWCELL ASSEMBLY (00-1527)






Page 6 of 12 SS-Q45H-65, RK (4/12)




ATI-004

## SUBMERSIBLE SENSOR DIMENSIONS




# SUBMERSIBLE SENSOR INSTALLATION



ATI-0155

SS-Q45H-65, RK (4/12) Page 7 of 12

### **ELECTRICAL CONNECTIONS - 2-WIRE TRANSMITTER**



NOTES: 1. Voltage between Terminals 12 & 13 MUST be between 16 & 35 VDC.

2. Earth ground into Terminal 15 is HIGHLY recommended. This connection can greatly improve stability in electrically noisy environments.


ATI-0658

SS-Q45H-65, RK (4/12)

Page 8 of 12



### **SENSOR CONNECTIONS - REMOTE JUNCTION BOX**




ATI-0714


SS-Q45H-65, RK (4/12) Page 9 of 12




## **Q22 pH SENSOR DIMENSIONS**



## pH SENSOR (BAYONET STYLE) DIMENSIONS




## SPECIAL APPLICATION FLOWCELLS (CONSULT FACTORY)



SS-Q45H-65, RK (4/12) Page 10 of 12



## **OPTIONAL PH SENSOR CONNECTIONS**




ATI-0660

SS-Q45H-65, RK (4/12) Page 11 of 12



# SENSOR CONNECTIONS - CIO, / pH WITH JUNCTION BOX

### (63-0101) Bayonet Style pH Probe <u>CANNOT</u> be used in a remote application



ATI-0716