








# PNEUMATIC PROPORTIONAL VALVES
















## Product Index



control	pipe connections							pad mount	pressure range (bar)	flow at 6 bar l/min (ANR)	filtration (µm)	hysteresis	vacuum	safety	technology	special feature	ATEX	type	illustration	series	page
	pressure	flow	M5	1/8	1/4	3/8	1/2														
<b>Proportional valves</b>																					
●				☒	☒	☒		☒	0-3 0-6 0-10	470 5200	50	< 1%		pression maintenue		digital control		SENTRONIC <sup>LP</sup>		<a href="#">617</a>	<a href="#">1</a>
●				☒	☒	☒		☒	0-3 0-6 0-10	470-1300	50	< 1%				digital electronics		SENTRONIC <sup>D</sup>		<a href="#">608</a> <a href="#">609</a>	<a href="#">7</a>
●				☒	☒		☒	☒	0-50	up to 5600	50	< 0,5%	●	pressure released	poppet	digital electronics	☒	SENTRONIC <sup>PLUS</sup>		<a href="#">614</a>	<a href="#">13</a>
●				☒	☒		☒	☒	0-50	up to 5600	50	< 0,5%	●			with external pneumatic pressure supply	☒	SENTRONIC <sup>PLUS</sup>		<a href="#">614</a>	<a href="#">19</a>
●					☒				0-3 0-6 0-10	1200	-	< 0,5%		pressure hold pressure release	pilot + booster	high-definition with digital control		SENTRONIC <sup>HD</sup>		<a href="#">616</a>	<a href="#">25</a>
	●					☒			0 - 8	20-500	-	< 2%		pressure released	poppet	with integrated control electronics		FLOWTRONIC <sup>D</sup>		<a href="#">607</a>	<a href="#">33</a>
●							☒		0-40	0 to 1700	50	< 0,5%		pressure released	spool	digital electronics		Servotronic Digital		<a href="#">615</a>	<a href="#">35</a>

00258GB-2017/R01  
Availability, design and specifications are subject to change without notice. All rights reserved.

All leaflets are available on: [www.asco.com](http://www.asco.com)

control		pipe connections							pad mount	pressure range (bar)	flow at 6 bar l/min (ANR)	filtration (µm)	hysteresis	safety	technology	type	illustration	series	page	
pressure	flow	 - instant fittings, O.D. (mm)	 - internal thread	 - pad mount	4	M5	1/8	1/4												3/8
<b>Mini piezo-valve</b>																				
●											0-8	0,086- 0,12	5	10 to 15%		multi-layer piezo ceramics	Piezotronic		<a href="#">630</a>	<a href="#">31</a>
<b>Proportional solenoid valve</b>																				
●											0-16	700-5600	50	-	pressure released		without control electronics		<a href="#">602</a>	<a href="#">29</a>
<b>Accessories</b>																				
●	●															Control device for proportional solenoid valve control	CONTROL <i>D</i>		<a href="#">603</a>	<a href="#">37</a>
																Digital control unit			<a href="#">908</a>	<a href="#">39</a>
																Electronic proportional control unit			<a href="#">908</a>	<a href="#">41</a>