



364 Stainless Steel Spool Valves

1/4" NPT 316L Compact 3-Way Valves

Applications

- Ideal for Oil and Gas Control Panel Applications
- Solenoid, Pneumatic and Manually Operated Options
- Upstream Oil and Gas Operations

Features & Benefits

- **Drop-In Replacement Design**
 - Compatible with most existing applications which eliminates the need to modify existing designs
- **Quick Delivery**
 - Popular constructions are available in the ASCO SameDay or ASCO 5Day shipping program which allows for fast part replacement and greater availability
- **ASCO's Proven Solenoid Valve Technology and Reliability**
 - Low power options, 1.4 and 1.8 watt constructions
 - UL/CSA approvals for Hazardous Locations, Class I Div. 1
 - Solenoid options with factory sealed leads reduce installation time
- **Corrosion Resistant**
 - 316L Stainless Steel valve materials offer longer life in harsh environments
 - NACE compliant (non solenoid versions only)
- **Extensive Manual, Pneumatic, and Solenoid Options**
 - 3-way valves with the following options offer a broad range of applications:

- Single Solenoid	- Air Pilot	- Indicator (Latch Option)
- Dual Solenoid	- Spring Return	- Air Pilot Return
- Straight Solenoid	- Push Button (Guarded / Unguarded)	- Remote Air Latch Pilot
- 90° Solenoid	- Palm Button (Latch Option)	



Specifications

- **Flow rate**
 - Normally Closed: Cv=1.6
 - Normally Open: Cv=1.1
- **Media**
 - Air, Inert Gas, and Sweet Dry Natural Gas (*consult factory for additional media*)
- **Wide Temperature Range**
 - Non Solenoid: -10°F to 200°F (-23°C to 95°C)
 - Solenoid options see table below

Solenoid	Voltage	Power	Min. Temperature	Max. Temperature
Low Power	24 VDC	1.4	-10°F (-23°C)	140°F (60°C)
Compact Low Power		1.8	-10°F (-23°C)	200°F (95°C)

